

EL 465855441

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

* * * * *

Methods of Forming Aluminum-Comprising Physical Vapor Deposition Targets; Sputtered Films; and Target Constructions

* * * * *

INVENTORS

Vladimir M. Segal
Jianxing Li
Frank Alford
Stephane Ferrasse

ATTORNEY'S DOCKET NO. 30-5022(4015)

**Methods of Forming Aluminum-Comprising Physical Vapor Deposition Targets;
Sputtered Films; and Target Constructions**

RELATED APPLICATION DATA

- 5 This application claims priority to U.S. provisional application Serial No.
60/193,354, which was filed March 28, 2000.

TECHNICAL FIELD

- 10 The invention pertains to methods of forming aluminum-comprising physical
vapor deposition targets, and to target constructions. In particular applications, the
invention pertains to methods of utilizing equal channel angular extrusion (ECAE) to
deform an aluminum-comprising mass in forming a physical vapor deposition (PVD)
target for use in the manufacture of flat panel displays (FPDs), such as, for example,
liquid crystal displays (LCDs).

15

BACKGROUND OF THE INVENTION

- 20 PVD is a technology by which thin metallic and/or ceramic layers can be
sputter-deposited onto a substrate. Sputtered materials come from a target, which
serves generally as a cathode in a standard radio-frequency (RF) and/or direct current
(DC) sputtering apparatus. For example, PVD is widely used in the semiconductor
industry to produce integrated circuits.

- 25 A relatively new application for sputtering technologies is fabrication of FPDs,
such as, for example, LCDs. The LCD market has experienced rapid growth. This
trend may accelerate in the next few years due to the diversified applications of LCDs
in, for example the markets of laptop personal computers (PCs), PC monitors, mobile
devices, cellular phones and LCD televisions.

Aluminum can be a particularly useful metal in forming LCDs, and it accordingly can be desired to form aluminum-comprising physical vapor deposition targets. The targets can contain a small content (less than or equal to about 100 parts per million (ppm)) of doping elements. The aluminum, with or without small additions of dopants, is generally desired to be deposited to form a layer of about 300nm which constitutes the reflecting electrode of LCD devices. Several factors are important in sputter deposition of a uniform layer of aluminum having desired properties for LCD devices. Such factors including: sputtering rate; thin film uniformity; and microstructure. Improvements are desired in the metallurgy of LCD aluminum targets to improve the above-discussed factors.

LCD targets are quite large in size, a typical size being 860 x 910 x 19 mm³, and are expected to become bigger in the future. Such massive dimensions present challenges to the development of tooling and processing for fabrication of suitable aluminum-comprising targets.

Various works demonstrate that three fundamental factors of a target can influence sputtering performance. The first factor is the grain size of the material, i.e. the smallest constitutive part of a polycrystalline metal possessing a continuous crystal lattice. Grain size ranges are usually from several millimeters to a few tenths of microns; depending on metal nature, composition, and processing history. It is believed that finer and more homogeneous grain sizes improve thin film uniformity, sputtering yield and deposition rate, while reducing arcing. The second factor is target texture. The continuous crystal lattice of each grain is oriented in a specific way relative to the plane of target surface. The sum of all the particular grain orientations defines the overall target orientation. When no particular target orientation dominates, the texture is considered to be a random structure. Like grain size, crystallographic

texture can strongly depend on the preliminary thermomechanical treatment, as well as on the nature and composition of a given metal. Crystallographic textures can influence thin film uniformity and sputtering rate. The third factor is the size and distribution of structural components, such as second phase precipitates and particles, and casting defects (such as, for example, voids or pores). These structural components are usually not desired and can be sources for arcing as well as contamination of thin films.

In order to improve the manufacture of LCD targets it would be desirable to accomplish one or more of the following relative to aluminum-based target materials:

- (1) to achieve predominate and uniform grain sizes within the target materials of less than 100 μm ; (2) to have the target materials consist of (or consist essentially of) high purity aluminum (i.e. aluminum of at least 99.99% (4N) purity, and preferably at least 99.999% (5N) purity, with the percentages being atomic percentages); (3) to keep oxygen content within the target materials low; and (4) to achieve large target sizes utilizing the target materials.

The thermomechanical processes (TMP) used traditionally to fabricate LCD targets can generally only achieve grain sizes larger than 200 μm for 5N Al with or without dopants. Such TMP processes involve the different steps of casting, heat treatment, forming by rolling or forging, annealing and final fabrication of the LCD target. Because forging and rolling operations change the shape of billets by reducing their thickness, practically attainable strains in today's TMP processes are restricted. Further, rolling and forging operations generally produce non-uniform straining throughout a billet.

The optimal method for refining the structure of high purity aluminum alloys (such as, for example, 99.9995% aluminum) would be intensive plastic deformation

sufficient to initiate and complete self-recrystallization at room temperature immediately after cold working.

High purity aluminum is typically provided as a cast ingot with coarse dendrite structures (Fig. 1 illustrates a typical structure of as-cast 99.9995% aluminum).

5 Forging and/or rolling operations are utilized to deform the cast ingots into target blanks. Flat panel display target blanks are optimally to be in the form of large thin plates. The total strains which can be obtained for any combination of forging and/or rolling operations can be expressed as $\epsilon = (1-h/H_0) * 100\%$; where H_0 is an ingot length, and h is a target blank thickness. Calculations show that possible thickness
10 reductions for conventional processes range from about 85% to about 92%, depending on target blank size to thickness ratio. The thickness reduction defines the strain induced in a material. Higher thickness reductions indicate more strain, and accordingly can indicate smaller grain sizes. The conventional reductions of 85% to 92% can provide static recrystallization of high purity aluminum (for instance,
15 aluminum having a purity of 99.9995% or greater) but they are not sufficient to develop the fine and uniform grain structure desired for flat panel display target materials. For example, an average grain size after 95% rolling reduction is about 150 microns (such is shown in Fig. 2). Such grain size is larger than that which would optimally be desired for a flat panel display. Further, the structures achieved by
20 conventional processes are not stable. Specifically, if the structures are heated to a temperature of 150°C or greater (which is a typical temperature for sputtering operations), the average grain size of the structures can grow to 280 microns or more (see Fig. 3). Such behavior occurs even after intensive forging or rolling.

Fig. 4 summarizes results obtained for a prior art high purity aluminum
25 material. Specifically, Fig. 4 shows a curve 10 comprising a relationship between a

percentage of rolling reduction and grain size (in microns). A solid part of curve 10 shows an effect of rolling reduction on a 99.9995% aluminum material which is self-recrystallized at room temperature. As can be seen, even a high rolling reduction of 95% results in an average grain size of about 160 microns (point 12), which is a relatively coarse and non-uniform structure. Annealing at 150°C for 1 hour significantly increases the grain size to 270 microns (point 14). An increase of reduction to 99% can reduce the grain size to 110 microns (point 16 of Fig. 4), but heating to 150°C for 1 hour increases the average grain size to 170 microns (point 18 of Fig. 4).

Attempts have been made to stabilize recrystallized high purity aluminum structures by adding low amounts of different doping elements (such as silicon, titanium and scandium) to the materials. A difficulty that occurs when the doping elements are incorporated is that full self-recrystallization can generally not be obtained for an entirety of the material, and instead partial recrystallization is observed along grain boundaries and triple joints. For example, the structure of a material comprising 99.9995% aluminum with 30 ppm Si doping is only partly recrystallized after rolling with a high reduction of 95% (see Fig. 6) in contrast to the fully recrystallized structure formed after similar rolling of a pure material (see Fig. 2). Accordingly, additional annealing of the rolled material at a temperature of 150°C for about 1 hour is typically desired to obtain a fully recrystallized doped structure. Such results in coarse and non-uniform grains (see Fig. 7).

Fig. 5 illustrates data obtained for 99.9995% aluminum with a 30 ppm silicon dopant. The curve 20 of Fig. 5 conforms to experimental data of 99.9995% aluminum with 30 ppm silicon after rolling with different reductions. A dashed part of the curve corresponds to partial self-recrystallization after rolling, while a solid part of the

curve corresponds to full self-recrystallization. The full self-recrystallization is attained after intensive reductions of more than 97%, which are practically not available in commercial target fabrication processes. The point 22 shows the average grain size achieved for the as-deformed material as being about 250 microns, and the point 24 shows that the grain size reduces to about 180 microns after the material is annealed at 150°C for 1 hour. The points 22 and 24 of Fig. 5 correspond to the structures of Figs. 6 and 7.

For the reasons discussed above, conventional metal-treatment procedures are incapable of developing the fine grain size and stable microstructures desired in high purity aluminum target materials for utilization in flat panel display technologies. For instance, a difficulty exists in that conventional deformation techniques are not generally capable of forming thermally stable grain sizes of less than 150 microns for both doped and non-doped conditions of high purity metals. Also, particular processing environments can create further problems associated with conventional metal-treatment processes. Specifically, there is a motivation to use cold deformation as much as possible to refine structure, which can remove advantages of hot processing of cast materials for healing pores and voids, and for eliminating other casting defects. Such defects are difficult, if not impossible, to remove by cold deformation, and some of them can even be enlarged during cold deformation. Accordingly, it would be desirable to develop methodologies in which casting defects can be removed, and yet which achieve desired small grain sizes and stable microstructures.

SUMMARY OF THE INVENTION

In one aspect, the invention includes a method of forming an aluminum-

comprising physical vapor deposition target. An aluminum-comprising mass is deformed by equal channel angular extrusion, with the mass being at least 99.99% aluminum and further comprising less than or equal to about 1,000 ppm of one or more dopant materials comprising elements selected from the group consisting of Ac, Ag, As, B, Ba, Be, Bi, C, Ca, Cd, Ce, Co, Cr, Cu, Dy, Er, Eu, Fe, Ga, Gd, Ge, Hf, Ho, In, Ir, La, Lu, Mg, Mn, Mo, N, Nb, Nd, Ni, O, Os, P, Pb, Pd, Pm, Po, Pr, Pt, Pu, Ra, Rf, Rh, Ru, S, Sb, Sc, Se, Si, Sm, Sn, Sr, Ta, Tb, Te, Ti, Tl, Tm, V, W, Y, Yb, Zn and Zr. After the aluminum-comprising mass is deformed, the mass is shaped into at least a portion of a sputtering target. The sputtering target can ultimately be formed to be either a monolithic or mosaic sputtering target.

In another aspect, the invention encompasses a method of forming an aluminum-comprising physical vapor deposition target which is suitable for sputtering aluminum-comprising material to form an LCD device. An aluminum-comprising mass is deformed by equal channel angular extrusion. After the mass is deformed, it is shaped into at least a portion of a physical vapor deposition target. The physical vapor deposition target has an average grain size of less than or equal to 45 microns.

In yet another aspect, the invention encompasses a physical vapor deposition target consisting essentially of aluminum and less than or equal to 1,000 ppm of one or more dopant materials comprising elements selected from the group consisting of Ac, Ag, As, B, Ba, Be, Bi, C, Ca, Cd, Ce, Co, Cr, Cu, Dy, Er, Eu, Fe, Ga, Gd, Ge, Hf, Ho, In, Ir, La, Lu, Mg, Mn, Mo, N, Nb, Nd, Ni, O, Os, P, Pb, Pd, Pm, Po, Pr, Pt, Pu, Ra, Rf, Rh, Ru, S, Sb, Sc, Se, Si, Sm, Sn, Sr, Ta, Tb, Te, Ti, Tl, Tm, V, W, Y, Yb, Zn and Zr. The physical vapor deposition target has an average grain size of less than or equal to 100 microns.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the invention are described below with reference to the following accompanying drawings.

Fig. 1 is an optical micrograph of a cast structure of 99.9995% aluminum
5 (magnified 50 times).

Fig. 2 is an optical micrograph of 99.9995% aluminum showing a self-recrystallized structure after 95% cold rolling reduction (magnified 50 times).

Fig. 3 is an optical micrograph of 99.9995% aluminum illustrating a structure achieved after 95% cold rolling reduction and annealing at 150°C for 1 hour
10 (magnified 50 times).

Fig. 4 is a graph illustrating an effect of prior art rolling reduction processes on grain size of 99.9995% aluminum which is self-recrystallized at room temperature.

Fig. 5 is a graph illustrating the effect of prior art rolling reduction on grain size of a material comprising 99.9995% aluminum with 30 ppm Si, with such material
15 being partly self-recrystallized at room temperature.

Fig. 6 is an optical micrograph of 99.9995% aluminum plus 30 ppm Si after 90% cold rolling reduction (magnified 50 times).

Fig. 7 is an optical micrograph of 99.9995% aluminum plus 30 ppm Si after 90% cold rolling reduction and annealing at 150°C for 1 hour (magnified 50 times).

Fig. 8 shows a flow chart diagram of a method encompassed by the present invention.

Fig. 9 is an optical micrograph showing the structure of 99.9995% aluminum after 2 passes through an equal channel angular extrusion (ECAE) device (magnified 50 times).

Fig. 10 is an optical micrograph of 99.9995% aluminum after 6 passes through an ECAE device (magnified 50 times).

Fig. 11 is a graph illustrating the effect of ECAE on grain size of 99.9995% aluminum which is self-recrystallized at room temperature.

5 Fig. 12 is a graph illustrating the effect of ECAE passes on grain size of a material comprising 99.9995% aluminum and 30 ppm Si. The graph illustrates the grain size after self-recrystallization of the material at room temperature.

Fig. 13 is an optical micrograph showing the structure of a material comprising 99.9995% aluminum and 30 ppm Si after 6 passes through an ECAE device
10 (magnified 100 times).

Fig. 14 is an optical micrograph showing the structure of a material comprising 99.9995% aluminum and 30 ppm Si after 6 passes through an ECAE device, 85% cold rolling reduction, and annealing at 150°C for 16 hours (magnified 100 times).

Figs. 15A and 15B show optical micrographs of a material comprising
15 aluminum and 10 ppm Sc after 6 ECAE passes via route D (i.e., a route corresponding to billet rotation of 90° into a same direction after each pass through an ECAE device). Fig. 15A shows the material in the as-deformed state and Fig. 15B shows material after 85% rolling reduction in thickness.

Fig. 16 is a diagrammatic top-view of a tiled target assembly composed of nine
20 billets.

Fig. 17 is a diagrammatic cross-sectional side-view of the target assembly of Fig. 16 shown along the line 17-17.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

25 ~~A deformation technique known as equal channel angular extrusion (ECAE) is~~

Subair

Sub 91/

used with advantage for the manufacture of physical vapor deposition targets, and in particular aspects of the invention is utilized for the first time in the manufacture of FPD and LCD targets. The ECAE technique was developed by V.M. Segal, and is described in US Patents Nos. 5,400,633; 5,513,512; 5,600,989; and 5,590,390. The disclosure of the aforementioned patents is expressly incorporated herein by reference.

The general principle of ECAE is to utilize two intersecting channels of approximately identical cross-section and extrude a billet through the channels to induce deformations within the billet. The intersecting channels are preferably exactly identical in cross-section to the extent that "exactly identical" can be measured and fabricated into an ECAE apparatus. However, the term "approximately identical" is utilized herein to indicate that the cross-sections may be close to exactly identical, instead of exactly identical, due to, for example, limitations in fabrication technology utilized to form the intersecting channels.

An ECAE apparatus induces plastic deformation in a material passed through the apparatus. Plastic deformation is realized by simple shear, layer after layer, in a thin zone at a crossing plane of the intersecting channels of the apparatus. A useful feature of ECAE is that the billet shape and dimensions remain substantially unchanged during processing (with term "substantially unchanged" indicating that the dimensions remain unchanged to the extent that the intersecting channels have exactly identical cross-sections, and further indicating that the channels may not have exactly identical cross-sections).

The ECAE technique can have numerous advantages. Such advantages can include: strictly uniform and homogeneous straining; high deformation per pass; high accumulated strains achieved with multiple passes; different deformation routes, (i.e., changing of billet orientation at each pass of multiple passes can enable creation of

various textures and microstructures); and low load and pressure.

ECAE can enable a decrease in the grain size of high purity aluminum and aluminum alloys used for the manufacture of LCDs by at least a factor of three compared to conventional practices.

5 Various aspects of the present invention are significantly different from previous ECAE applications. Among the differences is that the present invention encompasses utilization of ECAE to deform high purity materials (such as, for example, aluminum having a purity of greater than 99.9995% as desired for FPD targets), in contrast to the metals and alloys that have previously been treated by
10 ECAE. High purity metals are typically not heat treatable, and ordinary processing steps like homogenizing, solutionizing and aging can be difficult, if not impossible, to satisfactorily apply with high purity metals. Further, the addition of low concentrations of dopants (i.e., the addition of less than 100 ppm of dopants) doesn't eliminate the difficulties encountered in working with high purity metals. However,
15 the present invention recognizes that a method for controlling structure of single-phase high purity materials is a thermo-mechanical treatment by deformation, annealing and recrystallization. Also, as high purity metals are generally not stable and cannot be refined by dynamic recrystallization in the same manner as alloys, the present invention recognizes that static recrystallization can be a more appropriate
20 methodology for annealing of high purity metals than dynamic recrystallization. When utilizing static recrystallization annealing of materials, it is preferred that the static recrystallization be conducted at the lowest temperature which will provide a fine grain size. If strain is increased to a high level within a material, such can reduce a static recrystallization temperature, with high strains leading to materials which can
25 be statically recrystallized at room temperature. Thus, self-recrystallization of the

materials can occur immediately after a cold working process. Such can be an optimal mechanism for inducing desired grain sizes, textures, and other microstructures within high purity metal physical vapor deposition target structures.

In one aspect, the present invention utilizes ECAE to form a physical vapor
 5 deposition target for LCD applications. The target comprises a body of aluminum with a purity greater than or equal to 99.99% (4N). The aluminum can be doped with less than or equal to about 1000 ppm of dopant materials. The dopant materials are not considered impurities relative to the doped aluminum, and accordingly the dopant concentrations are not considered in determining the purity of the aluminum. In other
 10 words, the percent purity of the aluminum does not factor in any dopant concentrations.

An exemplary target can comprise a body of aluminum having a purity greater than or equal to 99.9995%. A total amount of dopant material within the aluminum is typically between 5 ppm and 1,000 ppm, and more preferably between 10 ppm and
 15 100 ppm. The amount of doping should be at least the minimal amount assuring the stability of material microstructures during sputtering, and less than the minimum amount hindering the completion of full dynamic recrystallization during equal channel angular extrusion.

The dopant materials can, for example, comprise one or more elements
 20 selected from the group consisting of Ge, Group IIA elements, Group IIIA elements, Group VIA elements, Group VA elements, Group IIIB elements, Group IVB elements, Group VIB elements, Group VIII elements, and Rare Earth elements. Alternatively, the dopant materials can comprise one or more of Ac, Ag, As, B, Ba, Be, Bi, C, Ca, Cd, Ce, Co, Cr, Cu, Dy, Er, Eu, Fe, Ga, Gd, Ge, Hf, Ho, In, Ir, La, Lu, Mg, Mn, Mo,
 25 N, Nb, Nd, Ni, O, Os, P, Pb, Pd, Pm, Po, Pr, Pt, Pu, Ra, Rf, Rh, Ru, S, Sb, Sc, Se, Si,

Sm, Sn, Sr, Ta, Tb, Te, Ti, Tl, Tm, V, W, Y, Yb, Zn and Zr.

The elements of the dopant materials can be in either elemental or compound form within the materials. The dopant materials can be considered to comprise two different groups of materials. The first group comprises dopant materials having effectively no room temperature solid solubility relative to an aluminum matrix, and having no intermediate compounds. Such first type of dopant materials are Be, Ge and Si. The second type of dopant materials have effectively no room temperature solid solubility in aluminum, and are not toxic, refractory or precious metals, and further possess relatively high melting temperatures. The second type of materials include various elements selected from the Group IIA elements; the Group IIIB elements; the Group IVB elements; the Group VIB elements; the Group VIII elements; the Group IIIA elements; the Group VA elements; the Group VIA elements, and the Rare Earth elements (i.e., the lanthanides).

The dopant materials can be in the form of precipitates or solid solutions within the aluminum-material matrix. Preferably, the target is composed of aluminum with purity greater than or equal to 99.99% (4N), and with one or more dopant materials comprising elements selected from the group consisting of Si, Sc, Ti, and Hf.

The present invention can provide a physical vapor deposition target for LCD applications comprising a body of aluminum with purity greater than or equal to 99.99% (4N), alone or doped with less than 1000 ppm of dissimilar elements selected from a group consisting of one or more of Ac, Ag, As, B, Ba, Be, Bi, C, Ca, Cd, Ce, Co, Cr, Cu, Dy, Er, Eu, Fe, Ga, Gd, Ge, Hf, Ho, In, Ir, La, Lu, Mg, Mn, Mo, N, Nb, Nd, Ni, O, Os, P, Pb, Pd, Pm, Po, Pr, Pt, Pu, Ra, Rf, Rh, Ru, S, Sb, Sc, Se, Si, Sm, Sn, Sr, Ta, Tb, Te, Ti, Tl, Tm, V, W, Y, Yb, Zn and Zr. Further the target can consist of

aluminum and one or more of the listed dissimilar elements, or can consist essentially of aluminum and the one or more of the listed dissimilar elements.

The LCD target can be made of a body of Al with purity greater than 99.99% (4N), alone or doped with less 100 ppm of one or more dissimilar elements listed above, and the total doping content of any element listed above can be higher than the solubility limit of this element at the temperature at which ECAE is performed.

Particularly preferred materials for LCD targets consist of Al and less than 100 ppm of Si; Al and less than 100 ppm of Sc; Al and less than 100 ppm of Ti; or Al and less than 100 ppm of Hf.

10 A preferred LCD target possesses: a substantially homogeneous composition throughout; a substantial absence of pores, voids, inclusions and any other casting defects; a predominate and controlled grain size of less than about 50 micrometers; and a substantially uniform structure and controlled texture throughout. Very fine and uniform precipitates with average grain diameters of less than 0.5 micrometers can
15 also be present in a preferred target microstructure.

LCD physical vapor deposition targets of the present invention can be formed from a cast ingot comprising, consisting of, or consisting essentially of aluminum. The aluminum material can be extruded through a die possessing two contiguous channels of equal cross section intersecting each other at a certain angle. The ingot
20 material can also be subjected to annealing and/or processing with conventional target-forming processes such as rolling, cross-rolling or forging, and ultimately fabricated into a physical vapor deposition target shape. The extrusion step can be repeated several times via different deformation routes before final annealing, conventional processing and fabrication steps to produce very fine and uniform grain
25 sizes within a processed material, as well as to control texture strength and orientation

within the material.

Processes of the present invention can be applied to large flat panel display monolithic targets, or targets comprised of two or more segments.

Particular embodiments of the present invention pertain to formation of aluminum-comprising physical vapor deposition targets, such as, for example, formation of aluminum-comprising physical vapor deposition targets suitable for liquid crystal display (LCD) applications. Fig. 8 shows a flow-chart diagram of an exemplary process of the present invention. In a first step, an aluminum-comprising cast ingot is formed, and in a second step the ingot is subjected to thermo-mechanical processing. The material resulting from the thermo-mechanical processing is an aluminum-comprising mass. The mass is subsequently deformed by equal channel angular extrusion (ECAE). Such deformation can be accomplished by one or more passes through an ECAE apparatus. Exemplary ECAE apparatuses are described in U.S. Patent No.'s. 5,400,633; 5,513,512; 5,600,989; and 5,590,390. The aluminum-comprising mass can consist of aluminum, or can consist essentially of aluminum. The mass preferably comprises at least 99.99% aluminum. The mass can further comprise less than or equal to about 100 parts per million (ppm) of one or more dopant materials comprising elements selected from the group consisting of Ac, Ag, As, B, Ba, Be, Bi, C, Ca, Cd, Ce, Co, Cr, Cu, Dy, Er, Eu, Fe, Ga, Gd, Ge, Hf, Ho, In, Ir, La, Lu, Mg, Mn, Mo, N, Nb, Nd, Ni, O, Os, P, Pb, Pd, Pm, Po, Pr, Pt, Pu, Ra, Rf, Rh, Ru, S, Sb, Sc, Se, Si, Sm, Sn, Sr, Ta, Tb, Te, Ti, Tl, Tm, V, W, Y, Yb, Zn and Zr. The aluminum-comprising mass can consist of aluminum with less than or equal to about 100 ppm of one or more of the dopant materials described above, or consist essentially of aluminum with less than or equal to about 100 ppm of one or more of the dopant materials described above.

ECAE is utilized in methodology of the present invention for addressing problems found during formation of PVD targets of high-purity materials. ECAE is a process which utilizes a simple shear deformation mode, which is different from a dominant deformation mode achieved by uniaxial compression of forging or rolling.

5 In high purity metals, the intensive simple shear of ECAE can manifest itself by developing very thin and long shear bands. The strains achieved inside these bands can be many times larger than the strains achieved outside the bands. The shear bands occur along a crossing plane of the channels utilized during ECAE. If a processing speed is sufficiently low to eliminate adiabatic heating and flow localization at the

10 macro-scale, shear bands in pure metals can have a thickness of only a few microns with a near regular spacing between each other of a few tenths of a micron. The bands can be observed after a single ECAE pass. However, if the number of ECAE passes increases the spacing between shear bands can reduce to a stable size. The actual size can vary depending on the material being subjected to ECAE, and the purity of such

15 material. A strain inside of the shear bands can be equivalent to very high reductions (specifically, reductions of about 99.99% or more), and static recrystallization is immediately developed in the bands. The static recrystallization can lead to new fine grains growing in spacing between the bands.

Figs. 9 and 10 show fully recrystallized structures of 99.9995% aluminum

20 after ECAE with 2 passes and 6 passes, respectively. The grains within the material attained a stable size after 6 passes. Experiments have shown that processing with a route corresponding to billet rotation of 90° into a same direction after each pass can provide the most uniform and equiaxial recrystallized structures for high purity materials. Such route is defined as route "D" in accordance with the standard

definitions that have been utilized to described ECAE processing in previous publications.

Fig. 11 shows a curve 30 demonstrating the change manifested in grain size of a high-purity aluminum material subjected to varying numbers of ECAE passes. Curve 30 of Fig. 11 can be compared with the curve 10 of Fig. 4 to illustrate advantages in grain size reductions attained by an ECAE process relative to the conventional processes utilized to generate the curve 10 of Fig. 4.

The ECAE structures are found to not only have small grain sizes, but also to be stable during additional annealing to sputtering-type temperatures. For example, after annealing at 150°C for 1 hour, a material subjected to six ECAE passes shows only a relatively insignificant increase in grain size of from 40 microns (point 32 in Fig. 11) to 50 microns (point 34 in Fig. 11). However, the structures diagrammed at Fig. 11 were found to be relatively unstable when subjected to rolling procedures, even when the rolling procedures accomplished only moderate reductions. For instance, a significant increase of grain size from 40 microns after 6 ECAE passes to 160 microns occurred after rolling with the reduction of 75% (point 36 on Fig. 11).

Generally, ECAE can be effectively performed only when a ratio of billet size to thickness is from about 4 to 8, while flat panel display targets typically have a ratio of up to 100 or more. Accordingly, additional rolling of ECAE processed billets may be desired to fabricate the thin targets desired for FPD. Thus, it would be desirable to develop methodologies which avoided the structure coarsening evidenced by point 36 of Fig. 11. One way to avoid such structure coarsening is to eliminate rolling. This can be achieved if an ECAE processed billet has a sufficiently large size to fabricate FPD targets by splitting the billet thickness for a number of thin plates. However, this can be a complicated process since FPD targets have a typical size of 1000

millimeters, or larger; and ECAE of such large billets is typically not practical. Another method for incorporating ECAE processed billets into FPD targets is to fabricate mosaic targets by using a large number of small pieces cut from ECAE billets (see, for example, Figs. 16 and 17). However, mosaic targets are typically
 5 expensive to fabricate, and also typically do not provide good performance in sputtering applications.

Another method which can be utilized to avoid grain size growth within ECAE processed materials is to provide doping elements within the ECAE materials. However, while the addition of dopants can typically be utilized for structure
 10 refinement when static recrystallization is performed as a separate annealing operation at sufficiently high temperatures after mechanical working, it cannot generally be applied in the case of self-annealing at room temperature during or immediately after deformation performed by forging or rolling because the doping can make even heavily deformed structures more stable.

15 ECAE can be utilized for grain refinement of high purity metals, even if the metals have some dopant material therein. For instance, 99.9995% aluminum having 30 ppm of silicon therein is found to be almost fully recrystallized after 2 passes through an ECAE apparatus. If the material is subjected to 3 to 6 passes through the apparatus, it is found to have a fine and uniform structure, with such structure
 20 remaining substantially unchanged after 6 passes through the device. Fig. 12 illustrates a curve 50 corresponding to the change in grain size of 99.9995% aluminum having 30 ppm silicon therein, with various numbers of ECAE passes. A dashed part of curve 50 corresponds to partial recrystallization, and a solid part of curve 50 corresponds to full recrystallization at room temperature immediately after
 25 ECAE.

The structure after 6 passes is illustrated in Fig. 13. Such structure is a substantially perfectly recrystallized, uniform, very fine and equiaxial structure having an average grain size of about 15 microns. Such properties can provide exceptional stability of the structure during subsequent rolling and annealing. For instance, subsequent rolling with a reduction of up to 90%, and long-term annealing of about 16 hours at a temperature of 150°C causes only a moderate grain growth, with the resulting structure having an average grain size of about 30 microns. Further, structure uniformity is maintained, as illustrated in the optical micrograph of Fig. 14. Such stability of the small grain size microstructures achieved with ECAE is substantially different than what can be accomplished with conventional processes of forging, rolling or other deformation techniques. Accordingly, ECAE can provide improved methodology for fabricating high purity targets with fine and stable microstructures for physical vapor deposition applications. It is found that ECAE processing utilizing from 3 to 6 passes through an ECAE device is typically suitable for forming a physical vapor deposition target blank. In particular, ECAE with 4 passes of route "D" (i.e., rotation of 90° into the same direction after each pass) can be an optimal processing schedule.

Experiments have been performed on doping selection and concentration. Specifically, the doping elements Si, Sc and Ti have been tested. Concentrations ranged from 5 ppm to 100 ppm for each of the elements. In all of the tested cases, the effects achieved with the elements were found to be qualitatively about the same, with some quantitative differences. For instance, it was found that silicon doping can provide the best refinement, provided that a doping concentration is from about 5 ppm to about 100 ppm.

Among the benefits of utilizing ECAE for forming target blanks of high-purity materials, relative to utilizing conventional processes, is that ECAE can be utilized in combination with a hot-forging operation. Specifically, ECAE removes restrictions on attainable deformation during processing from a cast ingot to a target blank, and accordingly removes requirements on the original structures subjected to ECAE. A material can be subjected to hot forging prior to ECAE. Such hot forging can result in substantially entire elimination of casting defects, which can further result in improved performance of targets formed by methodology of the present invention relative to targets formed by conventional processes.

In a fourth step of the Fig. 8 flow-chart diagram, the deformed aluminum-comprising mass is shaped into a PVD target, or at least a portion of a target. Such shaping can comprise, for example, one or more of rolling, cross-rolling, forging, and cutting of the aluminum-comprising mass. The mass can be formed into a shape comprising an entirety of a physical vapor deposition target, or alternatively can be formed into a shape comprising only a portion of a physical vapor deposition target. An exemplary application wherein the mass is formed into a shape comprising only a portion of a physical vapor deposition target is an application in which the mass is utilized to form part of a so-called mosaic target. If the aluminum-comprising mass is utilized in a mosaic target, and further utilized for LCD applications, it can be desired that all of the various target portions of the mosaic target be aluminum-comprising masses which have been deformed by equal channel angular extrusion prior to incorporation into the mosaic target.

In the fifth step of the Fig. 8 process, the shaped mass is mounted to a backing plate to incorporate the mass into a target structure. Suitable backing plates and methodologies for mounting aluminum-comprising targets to backing plates are

known in the art. It is noted that the invention encompasses embodiments wherein an aluminum-comprising mass is utilized directly as a physical vapor deposition target without being first mounted to a backing plate, as well as embodiments in which the mass is mounted to a backing plate.

5 Processes of the present invention can be utilized to fabricate aluminum-comprising masses into targets having very fine and homogenous grain structures, with predominate sizes of the grains being less than about 50 micrometers. Such targets can be particularly suitable for sputtering applications in forming LCD materials. The present invention recognizes that improvements in grain refinement
10 can be provided by ECAE technology relative to processing of aluminum-comprising materials. The ECAE is preferably conducted at a temperature and speed sufficient to achieve desired microstructures and provide a uniform stress-strain state throughout a processed billet.

 The number of passes through an ECAE device, and the particular ECAE
15 deformation route selected for travel through the device can be chosen to optimize target microstructures. For instance, grain refinement can be a consequence of radical structural transformations occurring during intense straining by simple shear through an ECAE device.

 Figs. 15A illustrates grains obtained for aluminum + 10 ppm Sc after ECAE
20 processing. The grains shown in Fig. 15A have an average size of about 20 microns, and are relatively fine, equiaxial, and homogenous. The structure shown in Fig. 15A has an average grain size that is at least a factor of 3 smaller than the sizes produced by conventional target-forming methods.

 At least three different aspects of ECAE contribute to the remarkable reduction
25 of grain size and improvement of grain uniformity achieved by treating

aluminum-comprising masses in accordance with the present invention. These three aspects are an amount of plastic deformation imparted by ECAE, the ECAE deformation route, and simple shear forces occurring during ECAE.

After a material has been subjected to ECAE in accordance with methods of the present invention, the material can be shaped by conventional methods of forging, cross-rolling and rolling to form the material into a suitable shape to be utilized as a target in a sputtering process. The ultrafine grain sizes created during ECAE are found to remain stable and uniform, and to show limited grain growth upon further conventional processing; even during processing comprising a high reduction in thickness of a material. Such is exemplified by Fig. 15, which compares various microstructures of as-deformed ECAE samples (Fig. 15A) to those submitted to further unidirectional rolling at an 85% thickness reduction (Fig. 15B) for aluminum + 10 ppm Sc.

Preferably, traditional forming operations utilized for shaping a material after ECAE processing are conducted at temperatures which are less than those which will occur during sputtering. For instance, if sputtering processes are anticipated to occur at about 150°C, then conventional processing of, for example, rolling, cross-rolling, or forging occurring after ECAE will preferably occur at temperatures below 150°C. By conducting such processing at temperatures below the sputtering temperature, the likelihood of the conventional processing increasing grain sizes beyond those desired in a physical vapor deposition target is reduced. Typically, target shaping steps occur at temperatures of less than or equal to about 200°C, and more preferably occur at temperatures less than or equal to about 150°C, to keep the target shaping steps at temperatures below an ultimate sputtering temperature of a target.

The microstructures created during ECAE are found to exhibit exceptional stability upon annealing relative to microstructures created by conventional processes. For example, it is found that a sample of aluminum + 30 ppm Si which has been subjected to ECAE shows a limited and progressive increase in average grain size from approximately 12 microns to about 30 microns after annealing at 150°C for 1 hour. Such average grain size does not significantly change after annealing at 150°C for 16 hours. In contrast, samples submitted solely to rolling to an 85% reduction in thickness (a conventional process), show a dramatic grain growth up to average grain sizes larger than 250 micron after annealing at only 125°C for 1 hour.

Utilization of ECAE for processing aluminum targets can enable control of a texture within the targets, with the term "texture" referring to a crystallographic orientation within the target. If a large number (i.e. a vast majority) of the grains in a material have the same crystallographic orientation as one another, the material is referred to as having strong texture. In contrast, if the grains do not have the same crystallographic orientation, the material is referred to as having a weak texture. Note that the referred-to crystallographic orientation is not to imply that the grains are part of a single crystal. Various textures can be created utilizing methodology of the present invention.

A particular application of the invention is directed to the manufacture of targets of especially large size. Figs. 16 and 17 display this aspect of the invention. In Figs. 16 and 17, the construction of a target 190 in the form of a tiled assembly is provided. Such comprises joining two or more billets 200 of identical shape, dimensions and processing history to a backing plate 210, machining the surface of the resulting assembly, and fabricating the final target 190. Preferably, the backing plate is made of a high strength material and possesses a length and width close to

those of the final target. Joining is realized by known methods such as soldering, brazing, welding or diffusion bonding at an interface 220 between the backing plate and the bottom of each single billet and at sufficient time, pressure and temperature. Preferably, techniques such as brazing or soldering will be used because they can

5 utilize lower temperatures than some of the other methods. Also, lateral forces along the three different directions X, Y and Z shown in Figs 16 and 17 are exerted with appropriate tooling. The forces along the directions X and Y keep all the billets held tightly together, while the force along the Z direction participates to the joining operations and keeps the surface of the final target flat. Also, as shown in Figs. 16

10 and 17, one side of the bottom of each billet is preferably machined to leave a space 230 at the bottom between adjacent billets. Such space can have materials provided therein which are used for joining the billets together (the space is shown in dashed-line phantom view in Fig. 16). This space can also prevent the materials utilized for soldering, brazing, welding and diffusion bonding from going between billets and

15 contaminating the target surface and the volume to be sputtered.

The method described with reference to Figs. 16 and 17 can present several advantages for the production of very large targets. First, current equipment and tooling can be employed. Second, contrary to current known methods, intensive rolling and/or cross-rolling are not used to reach final target size; therefore, for

20 example, as-deformed ECAE billets can be directly joined together and retain their advantages in terms of grain size and texture. Third, the procedure is easily adaptable to any future evolution of the size of LCD targets.

EXAMPLES

Example 1: High-purity aluminum having 30 ppm Si therein, and processed in accordance with methodology of the present invention.

5 As-cast material defined as 5N5 Al and 30ppm Si is processed via hot forging at 75% reduction and ECAE for 6 passes via route D. The material has a fully recrystallized structure with grain size of 15 μm . Subsequent rolling with a reduction of 85% grew the average grain size to 20 μm with an aspect ratio of about 1.5. Annealing at a temperature of 150°C for 1 hour, which was estimated as the highest
10 temperature expected during a subsequent sputtering process, resulted in an insignificant grain growth to 23 μm . During a long (16 hours) exposure to 150°C, grains grew to 28 μm . Also, a temperature increase to 200°C for 1 hour yielded a similar grain size of about 30 μm . Therefore, ECAE plus rolling provides a fine and uniform structure for a material of 5N5 Al and 30ppm Si, with an average grain size
15 of less than or equal to about 30 μm which is stable for sputtering target applications.

Example 2: High-Purity Aluminum having 10 ppm silicon therein, and processed in accordance with methodology of the present invention.

20 Samples were cast, hot forged at 74% reduction and ECAE extruded for 6 passes via route D. A Structure after ECAE is fully dynamically recrystallized with an average grain size of about 19 μm . Subsequent rolling at 85%, and annealing at 150°C for 1 hour yields a fully recrystallized grain size of around 35 μm .

Example 3: High-Purity Aluminum having 10 ppm Sc therein, and processed in accordance with methodology of the present invention.

25 Samples were cast, hot forged at 74% reduction, and ECAE extruded for 6 passes via route D. A structure after ECAE is fully dynamically recrystallized with an

average grain size of about 26 μm . During rolling up to a reduction of 60%, the structure remains stable and typical for heavily-rolled materials. After 70% reduction, first recrystallized grains are observed. At 85% rolling reduction, about 60% of the sample area was fully recrystallized with an average grain size of about 45 μm .

5

Example 4: Aluminum having 30 ppm silicon therein, and processed in accordance with prior art technologies.

The present example was run to allow comparison of previous results of ECAE (examples 1-3) with data obtained utilizing conventional processing technologies. The same 5N5 Al+30ppm Si material was used for this example as was used in Example 1. A cast, hot forged at 74% reduction and annealed sample was subsequently cold rolled with a reduction of 85%. Its structure is not fully recrystallized and fine dynamically recrystallized grains can be observed only along boundaries of original grains. Additional annealing at 125°C for 1 hour provides full recrystallization but the microstructure has a highly non-uniform distribution with an average grain size of about 150 μm . Annealing at higher temperatures further increases the average grain size. The example illustrates that conventional processing techniques only provide a moderate refinement of the structure of 5N5 Al with 30 ppm Si doping. Specifically, the grain size achieved is well above a desired limit of 100 μm , and, in fact, is greater than 150 μm .

In compliance with the statute, the invention has been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the invention is not limited to the specific features shown and described, since the means herein disclosed comprise preferred forms of putting the invention



into effect. The invention is, therefore, claimed in any of its forms or modifications within the proper scope of the appended claims appropriately interpreted in accordance with the doctrine of equivalents.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
22